

CYCLE 2021-07

Second version: WN 1134 (NL new suspension request) and WN 0011 (BE new suspension request) were added to the list.

Sorting order:

A – first 'quotas', then 'suspensions'

B – **new** requests, **amending** requests

>>>>The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group.

Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic<<<<

CN code	TARIC	Reference Mail	Working Number	Description	S/Q	New or amendment request	Measure status	Partner Position Country	Partner Position	Public Comments
0710 21 00		4921372/2020	1302	Peas in bulk of the species "Pisum Sativum", shelled and frozen, to be used, after cleaning and grading, in packaged food preparations	Q/ 5750tonnes, 01.07-31.12	New	UNDER EXAMINATION	IT	Applicant	Round 2021-07
2710 19 81 2710 19 99		4953221/2020 5153510/2020	1050	Catalytically hydroisomerized and dewaxed base oil of hydrogenated, highly isoparaaffinic hydrocarbons, containing: - 90 % or more by weight of saturates, and - not more than 0,03 % by weight of sulphur, and with: - a viscosity index of 80 or more, but less than 120, and a - kinematic viscosity of 5,0 cSt at 100°C or more, but not more than 13,0 cSt at 100°C	Q/ 713055tonnes, 01.07-31.12	New	UNDER EXAMINATION	BE DE	Applicant Applicant	Round 2021-7 Intended use: Lubricants
2850 00 20		4953282/2020	1052	Sodium borohydride (CAS RN 16940-66-2) with a purity by weight of 98 % or more, also as an aqueous stabilized solution with 30-	Q/ 1000tonnes, 01.07-31.12	New	UNDER EXAMINATION	DE	Applicant	Round 2021-7 -Strong reducing agent, also borane former -Strong reducing agent,

2903 22 00				40 % NaOH		Q/ 10500000 kilograms, 01.01-31.12	New	UNDER EXAMINATION	DE EU	Applicant Opposed	also with a bleaching effect
	2418770/2020	1902		Trichlorethylene (CAS RN 79-01-6) with a purity by weight of 99,7 % or more							Round 2021-07 - roll over request. Round 2021-01 REJECTION COM Machine Translation: Justification as a product with COVID- 19 reference: This is due to the fact that trichloroethylene is used as a raw material for HFC-134a, which is also used for medical purposes; here: for propulsion of asthma inhalation equipment. It is particularly important for asthma patients to be well served and properly adjusted in the COVID-19 pandemic.
2919 90 00	4958443/2020	1049		Tris(2-ethylhexyl) phosphate (CAS RN 78- 42-2) with a purity by weight of 99 % or more		Q/ 1000tonnes, 01.07-31.12	New	UNDER EXAMINATION	HU	Applicant	Round 2021-7 Used as a co-formulant in the herbicide products
2919 90 00	4958443/2020	1105		Tris(2-ethylhexyl) phosphate (CAS RN 78- 42-2) with a purity by weight of 99 % or more		Q/ 1000tonnes, 01.07-31.12	New	UNDER EXAMINATION	HU	Applicant	Round 01.07.2021 Used as a co-formulant in the herbicide products manufacture
3824 99 96	4636646/2020	1300		A mixture consisting of 49 % or more but not more than 50 % of polysulfides, bis[3- (triethoxysilyl)propyl] (CAS RN 211519-85- 6) with 50 % or more but not more than 51 % of Carbon Black (CAS RN 1333-86-4)		Q/ 2000tonnes, 01.07-31.12	New	UNDER EXAMINATION	IE	Applicant	Round 2021-07 used in the manufacture of tires for passenger cars

7410 11 00		4953136/2020	1140	Bare Copper Foil in rolls - with a purity of copper from 99-99,8 % - of a thickness of 6-8 um for use in the manufacturing of lithium-ion electric rechargeable batteries (1)	Q/ 4374tonnes, 01.07-31.12	New	UNDER EXAMINATION	DE	Applicant	Round 01.07.2021 used in the manufacturing of lithium-ion electric rechargeable batteries
7601 10 00		4894571/2020	1122	Unalloyed, unwrought aluminium, typically more than 99 % pure	Q/ 400000tonnes, 01.07-31.12	New	UNDER EXAMINATION	TR	Applicant	Round 01.07.2021 Unalloyed, unwrought aluminium, typically more than 99 % pure
7601 20 20		4957000/2020	1102	Unwrought aluminium alloys in the form of slabs and billets	Q/ 90000tonnes, 01.07-31.12	New	UNDER EXAMINATION	TR	Applicant	Round 1.07.2021 used in sectors like transportation, building & construction, packaging, electronics & electronics, industrial products, consumer durables, defense industries, aviation
7601 20 80		4956932/2020	1103	Alloyed, unwrought aluminium, less than 99 % pure, not in the form of slabs or billets	Q/ 90000tonnes, 01.07-31.12	New	UNDER EXAMINATION	TR	Applicant	Round 01.07.2021 used in sectors like transportation, building & construction, packaging, electronics & electronics, industrial products, consumer durables, defense industries, aviation and others
7607 11 19		4955605/2020	1104	Aluminum foil in roll form for battery cell positive layer - purity of the aluminum ranges from 99-99,95 %, - of a thickness of 10-15 um, - with a surface oxide layer, for use in the manufacturing of lithium-ion electric rechargeable batteries (1)	Q/ 1500tonnes, 01.07-31.12	New	UNDER EXAMINATION	DE	Applicant	Round 01.07.2021 for use in the manufacturing of lithium-ion electric rechargeable batteries

8414 90 00		4867451/2020	1304	Turbocharger wheel housing of aluminium alloy foundry made - with a heat resistance up to 400°C - with a hole of 30 mm or more but not more than 300 mm for the insertion of the wheel	Q/ 200000pieces, 01.07-31.12	New	UNDER EXAMINATION	FR	Applicant	Round 2021-07 For production of ball bearing
8482 91 90		4867666/2020	1115	Rollers with a logarithmic profile and a diameter of 25 mm but not more than 70 mm or balls with a diameter of 30 mm but not more than 100 mm, - in 100Cr6 steel or 100CrMnSi6-4 steel, - with ultra sonic quality FBH 0,5 mm	Q/ 300000pieces, 01.07-31.12	New	UNDER EXAMINATION	FR	Applicant	Round 01.07.2021 used as component of blade bearings for wind turbine.
8482 99 00		4867593/2020	1114	Rings: - internal or external, - pre-machined, - with an external diameter of 1 000 mm but not more than 6 500 mm, - in alloy steel 42CrM04 or in alloy steel 42CrM04 NIC, - for ball bearing or roller bearing	Q/ 1500pieces, 01.07-31.12	New	UNDER EXAMINATION	FR	Applicant	Round 01.07.2021 Premachined rings

ex 2833 29 80	40	1589379/2017	3100	Caesium sulphate (CAS RN 10294-54-9) in solid form or as aqueous solution containing by weight 48 % or more but not more than 52 % of caesium sulphate	Q/ 400tonnes, 01.01-31.12	Amendment	UNDER EXAMINATION	DK	Applicant	Round 2021-07 - Request for increase. The final product is the catalyst
2912 42 00		1927/2/2003	3111	Ethylvanillin (3-ethoxy-4-hydroxybenzaldehyde) (CAS RN 121-32-4)	Q/ 2650tonnes, 01.01-31.12	Amendment	UNDER EXAMINATION	FR AT	Applicant Co-applicant	Round 2021-07- Request for increase. pour aliments et parfums
ex 2922 41 00	10	2544706/2019	3101	NL(15.09.2020) new proposal: L-Lysine hydrochloride (CAS RN 657-27-2) or an aqueous solution of L-lysine (CAS RN 56-87-1), containing by weight 50 % or more of L-lysine	Q/ 241000tonnes, 01.07-31.12	Amendment	UNDER EXAMINATION	NL AT DK FR	Applicant Co-applicant Co-applicant Opposed	Round 2021-07- Amendment + request for increase. Animal feed, either in the form of a pre-mix or as a final product

						---	Current text: L-Lysine hydrochloride (CAS RN 657-27-2)								
ex 2929 10 00	25	5933023/2019	2800				1,5-Naphthylene diisocyanate (CAS RN 3173-72-6) with a purity by weight of 90 % or more		Q/ 205tonnes, 01.07-31.12	Amendment	UNDER EXAMINATION	BE DE	Applicant Applicant	Round 2021-07 - Amendment. - used for wear pieces, coupling pieces, screen printing squeegee's and wheels with a semi- hard wheel tread.	
ex 8528 59 00	40	1578515/2019	3145				Electronic device with LCD touch screen display powered by a voltage of 12 V or more but not more than 14,4 V: - with LCD control processor, - with GPS module, - with Bluetooth module, - with USB port, - with radio signal tuner, - with functions for cooperation with E-CALL, - with connectors, - without integrated control panel, for use in the manufacture of goods of Chapter 87 (1)		Q/ 60000pieces, 01.07-31.12	Amendment	UNDER EXAMINATION	SK DE EU	Applicant Opposed Opposed	Round 2021-07 - objection. for use in the manufacture of goods of Chapter 87	

CN code	TARIC	Reference Mail	Working Number	Description	<u>Suspensions</u>	New or amendment request	Measure status	Partner Position Country	Partner Position	Public Comments
2710 12 25		4998385/2020	1364	Hydrocarbons, C6, n-alkanes, iso-alkanes, cycloalkanes, (EC No: 925-292-5) with n-hexane (CAS: 110-54-3) of not less than 60 %	S	New	UNDER EXAMINATION	PL	Applicant	Round 2021-07 Hexane is used as solvent in anionic polymerization of styrene and 1,3- butadiene, in production plant for synthesis of solution

2903 99 80												butadiene and styrene-butadiene rubbers (LiBR and SSBR).
												Round 2021-07 Intended use: Liquid crystal production
2903 99 80	4783905/2020		1109		4-(Trans-4-ethylcyclohexyl)bromobenzene (CAS RN 91538-82-8) of a purity by weight of 95 % or more	S		New		UNDER EXAMINATION	DE	Applicant
2903 99 80	4783940/2020		1047		4-(Trans-4-propylcyclohexyl)bromobenzene (CAS RN 86579-53-5) with a purity by weight of 95 % or more	S		New		UNDER EXAMINATION	DE	Applicant
2906 11 00	4998346/2020		1051		Sodium mentholate 50 % solution in solvent naphtha (petroleum), light aliphatic: - sodium mentholate, (cyclohexanol, 5-methyl-2-(1-methylethyl), sodium salt, (1R,2S,5R)-rel-), (CAS RN 19321-38-1) - light aliphatic solvent naphtha (petroleum) (CAS RN 64742-89-8)	S		New		UNDER EXAMINATION	PL	Applicant
2910 90 00	4670964/2020		1013		(R)-oxiran-2-ylmethyl 3-nitrobenzenesulfonate (CAS RN 115314-17-5) with a purity by weight of 97 % or more	S		New		UNDER EXAMINATION	ES	Applicant
2912 19 00	4930480/2020		1044		Acrylaldehyde (CAS RN 107-02-8) with a purity by weight of 98 % or more	S		New		UNDER EXAMINATION	FR	Applicant
2914 29 00	4805216/2020		1029		4-Propylcyclohexanone (CAS RN 40649-36-3) with a purity by weight of 95 % or more	S		New		UNDER EXAMINATION	DE	Applicant
2915 90 70	5337122/2020		0011		Tin bis(2-ethyl hexanoat) (CAS RN 301-10-0) with a purity by weight of 97 % or more	S		New		UNDER EXAMINATION	BE	Applicant
												Round 2021-7 used in the reaction of polyether-polyurethane

												foam, and as a urethane foam plastic antioxidant
2916 20 00			4805136/2020	1028	Cyclopentanecarboxylic acid (CAS RN 3400-45-1) with a purity by weight of 98 % or more	S	New		UNDER EXAMINATION	ES	Applicant	Round 2021-07 Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity).
2916 39 90			4659417/2020	1010	(2,5-dibromophenyl)acetic acid (CAS RN 203314-28-7) with a purity by weight of 98,0 % or more	S	New		UNDER EXAMINATION	IT	Applicant	Round 2021-07 Used in the synthesis of pharmaceutical intermediates and active pharmaceutical ingredients.
2916 39 90			4671184/2020	1015	(R)-tert-butyl 2'-((1-(hydroxyethyl)-3-methyl-[1,1'-biphenyl]-4-carboxylate (CAS RN 1246560-92-8) with a purity by weight of 98 % or more	S	New		UNDER EXAMINATION	ES	Applicant	Round 2021-07 Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity).
2917 39 95			5011386/2020	1056	2,3-Pyrazinedicarboxylic anhydride (CAS RN 4744-50-7) with a purity by weight of 85 % or more	S	New		UNDER EXAMINATION	LV	Applicant	Round 2021-07 used for manufacturing of pharmaceutical
2918 29 00			4866972/2020	1036	2-[2-(2-([3-(3-Tert-butyl-4-hydroxy-5-methylphenyl)propanoyl]oxy)ethoxy)ethoxy]ethyl 3-(3-tert-butyl-4-hydroxy-5-methylphenyl)propanoate (CAS RN 36443-68-2) with a purity by weight of 96 % or more	S	New		UNDER EXAMINATION	IT	Applicant	Round 2021-07 used as stabilizer in styrene polymers, particularly impact-modified polystyrenes, ABS, MBS, SB as well as in POM homo- and co-polymers, polyurethanes, polyamides, thermoplastic

2918 30 00			4930610/2020	1046	Methyl 5-oxo-6,7,8,9-tetrahydro-5H-benzof[7]annulene-2-carboxylate (CAS RN 150192-89-5) with a purity by weight of 96,8 % or more	S	New	UNDER EXAMINATION	FR	Applicant	polyesters, PVC and other polymers. Round 2021-07 Chemical intermediate of active pharmaceutical ingredient for the manufacture of pharmaceutical product
2918 99 90			4867173/2020	1037	2-Bromo-5-methoxybenzoic acid (CAS RN 22921-68-2) with a purity by weight of 98,5 % or more	S	New	UNDER EXAMINATION	AT	Applicant	Round 2021-07 Use as raw material for the manufacture of a Pharmaintermediate.
2921 29 00			4867213/2020	1038	N1,N3-Diallylpropane-1,3-diamine dihydrochloride (CAS RN 205041-15-2) with a purity by weight of 96 % or more	S	New	UNDER EXAMINATION	AT	Applicant	Round 2021-07 Use as raw material for the manufacture of an active pharmaceutical ingredient
2921 29 00			4730881/2020	1016	(S)-propane-1,2-diamine dihydrochloride (CAS RN 19777-66-3) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	ES	Applicant	Round 2021-07 Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity).
2921 49 00			4805347/2020	1030	N-(9,9-Dimethyl-9H-fluoren-2-yl)-9,9-dimethyl-9H-fluoren-2-amine (CAS RN 500717-23-7) with a purity by weight of 95 % or more	S	New	UNDER EXAMINATION	DE	Applicant	Round 2021-07 Intended use: Organic light emitting diode (OLED) materials for displays
2924 19 00			4636242/2020	1001	N5-(Aminocarbonyl)-L-Ornithine 2-hydroxybutanedioate (CAS RN 70796-17-7) (1:1) with a purity by weight of 98,5 % or more	S	New	UNDER EXAMINATION	IE	Applicant	Round 2021-07 used in the manufacture of specific physiological management formulations with other

												ingredients (manufacture of health food and fitness work-out products).	
2924 19 00				4731187/2020	1020		Methyl N'6-(tert-butoxycarbonyl)-L-lysinate hydrochloride (CAS RN 2389-48-2) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	ES	Applicant	Round 2021-07 Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity).
2924 19 00				4636178/2020	1000		N5-(Aminocarbonyl)-L-Ornithine 2-hydroxybutanedioate (CAS RN 54940-97-5) (2:1) with a purity by weight of 98,5 % or more	S	New	UNDER EXAMINATION	IE	Applicant	Round 2021-07 used in the manufacture of specific physiological management formulations with other ingredients (manufacture of health food and fitness work-out products).
2924 19 00				4663799/2020	1012		1,3-Diethyl 2-acetamidopropanedioate (CAS RN 1068-90-2) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	IT	Applicant	Round 2021-07 The product is used as starting material for the production of an Active Pharmaceutical Ingredient.
2924 29 70				4805418/2020	1031		β-(2-Amino-2-oxoethyl)-4-chlorobenzenepropanoic acid (CAS RN 1141-23-7) of a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	DE	Applicant	Round 2021-07 Used as an intermediate chemical for manufacturing Baclofen as Pharmaceutical Active Ingredient.
2924 29 70				4671075/2020	1014		2-Chloro-N-(1-(4-chloro-3-fluorophenyl)-2-methylpropan-2-yl)acetamide (CAS RN 787585-35-7) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	ES	Applicant	Round 2021-07 Product used in the manufacturing of a

2930 90 98		4646322/2020	1007	weight of 79 % or more	S		New	UNDER EXAMINATION	IT	Applicant	Round 2021-07 used for the production of pharmaceutical.
2930 90 98		4900280/2020	1040	Benzyl (S)-2-amino-3-(3-(methylsulphonyl)phenyl)propanoate hydrochloride salt (CAS RN 1194550-59-8) with a purity by weight of 98 % or more	S		New	UNDER EXAMINATION	HU	Applicant	Round 2021-07 Use as an active ingredient for several herbicide products
2931 39 90		4813313/2020	1033	2-[4-(Methylsulfonyl)-2-nitrobenzoyl]cyclohexane-1,3-dione (CAS RN 104206-82-8) in wet cake form with a purity by weight of 74 % or more	S		New	UNDER EXAMINATION	DE	Applicant	Round 2021-07 Raw material for Flame retardants
2931 90 00		4813472/2020	1034	Tris(hydroxymethyl)phosphine oxide (CAS RN 1067-12-5) with a purity by weight of 85 % or more	S		New	UNDER EXAMINATION	DE	Applicant	Round 2021-07 Industrial Chemical Intermediate
2931 90 00		4751391/2020	1022	3-Isocyanatopropyltriethoxysilane (CAS RN 24801-88-5) with a purity by weight of 96 % or more	S		New	UNDER EXAMINATION	DE	Applicant	2021-7 used for manufacture of Active Pharmaceutical Ingredient
2932 99 00		4646271/2020	1006	Isaxomib citrate (INN) (CAS RN 1239908-20-3) with a purity by weight of 95 % or more	S		New	UNDER EXAMINATION	IT	Applicant	Round 2021-07 used for the production of pharmaceutical
2933 19 90		4730968/2020	1017	Benzofuran-6-carboxylic acid (CAS RN 77095-51-3) with a purity by weight of 98 % or more	S		New	UNDER EXAMINATION	ES	Applicant	Round 2021-07 Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity).

2933 29 90		5012021/2020	1054	6-(4-Benzylamino-3-nitrophenyl)-5-methyl-4,5-dihydro-2H-pyridazin-3-one (CAS RN 77469-62-6) with a purity by weight of 95 % or more	S	New	UNDER EXAMINATION	LV	Applicant	Round 2021-07 used for manufacturing of active pharmaceutical ingredient
2933 39 99		4867353/2020	1039	Oxalic acid-4-amino-3-(4-phenoxyphenyl)-1-[(3R)-piperidin-3-yl]-1,3-dihydro-2H-imidazo[4,5-c]pyridin-2-one (1/1) (CAS RN 1971921-35-3) with a purity by weight of 70 % or more of the product basis (without oxalic acid)	S	New	UNDER EXAMINATION	FR	Applicant	Round 2021-07 Chemical intermediate of active principle ingredient for the manufacture of pharmaceutical product
2933 39 99		4900505/2020	1043	Clodinafop-propargyl (ISO) (CAS RN 105512-06-9) with a purity by weight of 90 % or more	S	New	UNDER EXAMINATION	HU	Applicant	Round 2021-07 Use as an active ingredient for several herbicide products
2933 39 99		4930553/2020	1045	Tert-Butyl (3R)-3-(4-amino-2-oxo-2,3-dihydro-1H-imidazo[4,5-c]pyridin-1-yl)piperidine-1-carboxylate (CAS RN 1971921-33-1) with a purity by weight of 95 % or more	S	New	UNDER EXAMINATION	FR	Applicant	Round 2021-07 Chemical intermediate of active principle ingredient for the manufacture of pharmaceutical product
2933 39 99		5010775/2020	1057	1-Benzyl-4-phenylpiperidine-4-carbonitrile monohydrochloride (CAS RN 71258-18-9) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	SK	Applicant	Round 2021-07 used for manufacture of medical product
2933 49 10		4646381/2020	1008	2-(<i>tert</i> -butoxycarbonyl)-5,7-dichloro-1,2,3,4-tetrahydroisoquinoline-6-carboxylic acid (CAS RN 851784-82-2) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	IT	Applicant	Round 2021-07 used for the production of pharmaceutical
2933 59 95		4805091/2020	1027	2-Chloropyrimidine (CAS RN 1722-12-9) with a purity by weight of 98,5 % or more	S	New	UNDER EXAMINATION	ES	Applicant	Round 2021-07 It is a raw material for the manufacture, through a chemical synthesis, of an active pharmaceutical ingredient (API) intended for the manufacture of a

2933 79 00			4646452/2020	1009	1-Phenylloxindole (CAS RN 3335-98-6) with a purity by weight of 99,5 % or more	S	New	UNDER EXAMINATION	IT	Applicant	medicine for human use. Round 2021-07 used for the production of pharmaceutical
2933 99 80			4638197/2020	1003	1,2,4-Triazole (CAS RN 288-88-0) with a purity by weight of 99,9 % or more	S	New	UNDER EXAMINATION	IT	Applicant	Round 2021/7 used for the production of a key intermediate for the production of antiviral
2933 99 80			4817073/2020	1035	9-[1,1'-Biphenyl]-3-yl-9'-[1,1'-biphenyl]-4-yl-3,3'-bi-9H-carbazole (CAS RN 1643479-47-3) with a purity by weight of 95 % or more	S	New	UNDER EXAMINATION	DE	Applicant	Round 2021-07 used for liquid crystal production.
2933 99 80			4783989/2020	1024	5-Formyl-2,4-dimethyl-1H-pyrrole-3-carboxylic acid (CAS RN 253870-02-9) with a purity by weight of 96 % or more	S	New	UNDER EXAMINATION	ES	Applicant	Round 2021-07 Chemical compound intermediate for the manufacture of basic pharmaceutical compounds.
2933 99 80			4805004/2020	1025	2-Methylindoline (CAS RN 6872-06-6) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	ES	Applicant	Round 2021-07 It is a raw material for the manufacture, through a chemical synthesis, of an active pharmaceutical ingredient (API) intended for the manufacture of a medicine for human use.
2934 10 00			4900419/2020	1042	Thiamethoxam (ISO) (CAS RN 153719-23-4) with a purity by weight of 90 % or more	S	New	UNDER EXAMINATION	HU	Applicant	Round 2021-07 Use as an active ingredient for several herbicide products

2934 99 90		4638095/2020	1002	Uridine with a purity by weight of 98 % or more (CAS RN 58-96-8)	S	New	UNDER EXAMINATION	IT	Applicant	Round 2021-07 used for the production of a key intermediate for the production of antiviral
2934 99 90		4731097/2020	1019	1-(4-Aminophenyl)-5,6-dihydro-3-(4-morpholinyl)-2(1H)-pyridinone (CAS RN 1267610-26-3) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	ES	Applicant	Round 2021-07 Chemical compound intermediate for the manufacture of basic pharmaceutical compounds.
2934 99 90		4645272/2020	1005	<i>trans</i> -(+/-)-11-Chloro-2,3,3a,12b-tetrahydro-2-methyl-1H-dibenz[2,3:6,7]oxepino[4,5-c]pyrrol-1-one (CAS RN 129385-59-7) with a purity by weight of 99 % or more	S	New	UNDER EXAMINATION	IT	Applicant	Round 2021/7 used for the production of pharmaceutical
2934 99 90		4957647/2020	1048	Aqueous solution consisting by weight of - 0,0005 percent or more, but not more than 0,002 percent polyadenylic acid potassium salt (CAS RN 26763-19-9), - 0,020 percent or more, but not more than 0,030 percent sodium citrate (CAS RN 68-04-2)	S	New	UNDER EXAMINATION	NL	Applicant	Round 2021-07 Used for pharma
2935 90 90		4805049/2020	1026	4-Chloro-3-sulfamoylbenzoic acid (CAS RN 1205-30-7) with a purity by weight of 97 % or more	S	New	UNDER EXAMINATION	ES	Applicant	Round 2021-07 It is a raw material for the manufacture, through a chemical synthesis, of an active pharmaceutical ingredient (API) intended for the manufacture of a medicine for human use.
3208 90 19 3911 90 99		4944315/2020	1135	Mixture, containing by weight: - 30 % or more, but not more than 40 % of a copolymer of vinyl methyl ether and monobutyl maleate (CAS RN 25119-68-0),	S	New	UNDER EXAMINATION	NL	Applicant	Round 2021-07 used in oral care products

3801 10 00							- 10 % or more, but not more than 20 % of a copolymer of vinyl methyl ether and monoethyl maleate (CAS RN 25087-06-3), - 40 % or more, but not more than 55 % of ethanol (CAS RN 64-17-5), - 1 % or more, but not more than 7 % of 1-Butanol (CAS RN 71-39-3)	S	New		UNDER EXAMINATION	PL	Applicant	Round 2021-07 for production of batteries
						1363	Artificial graphite (CAS RN 7782-42-5) in powder form, with: - particle size represented by d50 value of 13,5 µm with tolerance $\pm$ 2,0, - Specific Surface Area ("BET") of 1,5 m²/g with tolerance $\pm$ 0,4, - tap density of 1,00 g/cm³ with tolerance $\pm$ 0,10, - Specific Discharge Capacity of 352,0 mAh/g with tolerance $\pm$ 3,5, - initial efficiency of 90,0 % or more							
3801 10 00						1060	Artificial graphite (CAS RN 7782-42-5) in powder form, with: - particle size represented by d50 value of 14,3 µm with tolerance $\pm$ 2,0, - Specific Surface Area ("BET") - 0,9 m²/g with tolerance $\pm$ 0,4, - tap density of 1,02 g/cm³ with tolerance $\pm$ 0,10, - Specific Discharge Capacity of 348,5 mAh/g or more, - initial efficiency of 91,0 % or more	S	New		UNDER EXAMINATION	PL	Applicant	Round 2021-07 for production of batteries
3801 10 00						1362	Artificial graphite (CAS RN 7782-42-5) in powder form, with: - particle size represented by d50 value of 18,0 µm with tolerance $\pm$ 2,0, - Specific Surface Area ("BET") of 0,8 m²/g with tolerance $\pm$ 0,4, - tap density of 1,00 g/cm³ with tolerance $\pm$ 0,20, - Specific Discharge Capacity of 348,0 mAh/g or more,	S	New		UNDER EXAMINATION	PL	Applicant	Round 2021-07 used in the production of batteries

3801 10 00			4998721/2020	1361	- initial efficiency of 91,5 % or more Artificial graphite (CAS RN 7782-42-5) in powder form, with: - particle size represented by d50 value of 16,2 µm with tolerance ± 2,0, - Specific Surface Area ("BET") of 0,9 m2/g with tolerance ± 0,4, - tap density of 1,00 g/cm³ with tolerance ± 0,20, - Specific Discharge Capacity of 346,0 mAh/g or more, - initial efficiency of 91,0 % or more	S		New	UNDER EXAMINATION	PL	Applicant	Round 2021-07 used in the production of batteries. active material of the production of anode (positive electrode) responsible for the battery capacity and energy density in Li-Ion batteries.
3824 99 92			5064665/2020	1350	Solution of not more than 20 % by weight of lithium hexafluorophosphate (CAS RN 21324-40-3) in a mixture of ethylene carbonate (CAS RN 96-49-1), dimethyl carbonate (CAS RN 616-38-6) and ethyl methyl carbonate (CAS RN 623-53-0)	S		New	UNDER EXAMINATION	DE	Applicant	Round 2021-07 used in production of batteries
3824 99 96			4874795/2020	1119	Lithium-ion battery cathode precursor materials (Ni_{0.5}Mn_{0.5}Co_{0.5}YAlZ)OH₂ or (Ni_{0.5}Mn_{0.5}Co_{0.5}YAlZ)O where (W+X+Y+Z)=1 and containing by weight not more than 2 % of inorganic crystal structure with: - (W+X+Y+Z)=1, - W>50 %, X>1 %, Y<13 % and X<5 %, - a particle size with D₅ < 2µm and D₉₅ < 45µm	S		New	UNDER EXAMINATION	DE EU	Applicant Opposed	Round 2021-07 for production of batteries. Lithium-ion battery cathode precursor materials
3824 99 96			4874294/2020	1118	Lithium-ion battery cathode materials consisting of the formula LiA(Ni_{0.5}W_{0.5}Mn_{0.5}Co_{0.5}YAlZ)O₂ and containing by weight not more than 2 % of inorganic crystal structure dopants and/or particle coatings with: - A > 1, - (W+X+Y+Z)=1, - W>50 %, X>1 %, Y<13 % and X<5 %, - a particle size with D₅ < 2µm and D₉₅ < 45 µm	S		New	UNDER EXAMINATION	DE	Applicant	Round 2021-07 used in production of batteries. Lithium-ion battery cathode materials

3824 99 96		5063896/2020	1351	Li2NiO2 containing less than 5 % LiOH and less than 5 % Li2CO3 and less than 15 % NiO	S	New	UNDER EXAMINATION	DE EU	Applicant Opposed	Round 2021-07 used for production of batteries
3902 30 00		4944241/2020	1132	Hydrogenated block copolymer of styrene and isoprene containing less than 37 % Styrene in one of the forms mentioned in note 6 (b) to Chapter 39	S	New	UNDER EXAMINATION	NL	Applicant	Round 2021-07 Hydrogenated block copolymer of styrene and isoprene
3905 91 00		4944356/2020	1136	Aqueous solution, containing by weight - 25 % or more, but not more than 35 % of a copolymer of vinyl caprolactam, vinyl pyrrolidone, N,N-dimethylaminopropyl methacrylamide and 3-(methacryloylamino)propyl lauryldimethylammonium chloride (CAS RN 748809-45-2) - 10 % or more, but not more than 16 % of ethanol (CAS RN 64-17-5) whether or not denatured with tert-butyl alcohol (CAS RN 75-65-0) and/or denatonium benzoate (CAS RN 3734-33-6)	S	New	UNDER EXAMINATION	NL	Applicant	Round 2021-07 used in cosmetic care such as hairstyling products, e.g. styling gel.
3905 91 00		4944266/2020	1133	Aqueous solution consisting by weight of - 10 % or more, but not more than 20 % of a copolymer of vinyl pyrrolidone, N,N-dimethylaminopropyl methacrylamide and 3-(methacryloylamino)propyl lauryldimethylammonium chloride (CAS RN 306769-73-3) - not more than 1 % preservatives	S	New	UNDER EXAMINATION	NL	Applicant	Round 2021-07 Applications include skin care and hair care products.
3905 91 00		4944280/2020	<u>1134</u>	Copolymer of vinylpyrrolidone, vinyl caprolactam and dimethylaminoethyl methacrylate (CAS RN 102972-64-5), whether or not in an aqueous solution containing by weight: - 27 % or more, but not more than 33 % copolymer (spec range on % solids is 28 % - 32 % for Advantage S solution) - not more than 1,5 % ethanol - not more than 1 % preservatives	S	New	UNDER EXAMINATION	NL	Applicant	Round 2021-07 for use in building applications such as synthetic plasters, tile adhesives and joint compounds

3905 91 00		4944382/2020	1137	Copolymer of vinylpyrrolidone, acrylic acid and dodecyl methacrylate (CAS RN 83210-95-0)	S	New	UNDER EXAMINATION	NL	Applicant	Round 2021-07 suitable for ink jet applications)
3910 00 00		5007486/2020	1058	Copolymer of 80 % dimethylsiloxane, 10 % methyl methacrylate and 10 % butyl acrylate in the form of a white powder	S	New	UNDER EXAMINATION	DE	Applicant	Round 2021-07 Component for the production of Bayblend Types, Makrolon Types, Macroblend Types
3917 31 00 3917 32 00 3917 39 00		4923101/2020	1125	Tubings with: - outer diameter of minimum 0,36 mm but not more than 3,2 mm, - inner diameter of minimum 0,02 mm but not more than 1,6 mm, - with tolerances $\pm 0,01$ to 0,025 mm for both inner- and outer diameter for tubing with outer diameter up to 1,6 mm, - with tolerances $\pm 0,075$ mm for both inner and outer diameter for tubing with outer diameter of 2 mm of more but not more than 3,2 mm, - pressure rate of minimum 30 up to 700 bar, - suitable for chemical solutions within the entire range of pH values (pH 0-14) and within the range of strong organic solvents used in chromatography, for use in manufacturing of chromatographic system (1)	S	New	UNDER EXAMINATION	SE	Applicant	Round 2021-07 for use in manufacturing of chromatographic system
3917 40 00		4923172/2020	1126	Plastic fittings (nuts and ferrules) and connectors supported with or without a stainless steel ring, pressure rate up to 1 140 bar for tubings with: - outer diameter of minimum 0,36 mm but not more than 3,2 mm, - inner diameter of minimum 0,02 mm but not more than 1,6 mm, - with tolerances $\pm 0,01$ to 0,025 mm for both inner- and outer diameter for tubing with outer diameter up to 1,6 mm,	S	New	UNDER EXAMINATION	SE	Applicant	Round 2021-07 for use in manufacturing of chromatographic system

7419 99 90 8507 90 80	1821756/2020	1900	Copper plate with: - a length of 36 mm or more but not more than 49 mm, - a width of 29,8 mm or more but not more than 45,2 mm, - a thickness of 0,18 mm or more but not more than 0,66 mm, equipped with a polypropylene tape with: - a length of 6,5 mm or more but not more than 16,5 mm, - a width of 39 mm or more but not more than 56 mm, - characteristic allowing to create solid joint with pouch external layer by melting process assuring leak and pressure proof sealing of cell - resistance to influence of electrolyte used as the negative output, to be laser welded to the Li-Ion battery cell, intended for electric cars (1)	S	New	UNDER EXAMINATION	PL DE EU	Applicant Opposed Opposed	Round 2021-07 - roll over request. Round 2021-01 - rejected. used as the negative output for manufacturing Li ion battery cells used in electric cars
8108 90 30	4867502/2020	1113	Wires of an alloy of titanium : - with a niobium content by weight of 42 % or more, but not more than 47 %, - with a diameter of not more than 6 mm, - complying with standard AMS 4982	S	New	UNDER EXAMINATION	FR	Applicant	Round 2021-07 Used for more strict heat and shear resistance. The end users are the airframers, air engine manufacturers
8412 90 80	4952758/2020	1138	Bedplate made of solution strengthened ductile iron castings (SSDI), with - a length of 3,5 m or more but not more than 4,3 m, - a width of 2 m or more but not more than 3,5 m, - a height of 1 m or more, but not more than 1,3 m, - a weight of 11 tons or more but not more than 20 tons for anchoring and aligning the drive train (gearbox, pedestal bearing, rotor shaft) of a wind turbine	S	New	UNDER EXAMINATION	DE	Applicant	Round 2021-07 or installation in wind turbines

8412 90 80		4751414/2020	1301	Gearbox support made of solution strengthened ductile iron castings (SSDI), with: - a diameter of 2 m or more, but not more than 5 m - a weight of 2 tons or more but not more than 7 tons as a support and load-carrying component between the gearbox and the bedplate of a wind turbine	S	New	UNDER EXAMINATION	DE	Applicant	Round 2021-07 for installation in wind turbines.
8414 30 20		4998764/2020	1360	Hermetic reciprocating compressor, for isobutane as refrigerant: • with the Resistance Start Capacitor Run (RSCR) single phase motor, • with the general coefficient of performance factor not higher than 1,5 at ASHRAE conditions, • of the maximum cooling capacity of 150 W or more but not more than 180 W, at ASHRAE conditions	S	New	UNDER EXAMINATION	PL	Applicant	Round 2021-07 For manufacture of household appliances.
8414 30 20		4893423/2020	1121	Hermetic reciprocating refrigeration compressor for isobutane as refrigerant: • with the brushless permanent magnet 3-phase motor, • having left side suction connection and Power Factor Correction (PFC) inverter feasible to work from 1300 up to 4500 rpm, • of the maximum cooling capacity of 150 W or more but not more than 240 W, at ASHRAE conditions	S	New	UNDER EXAMINATION	PL	Applicant	Round 2021-07 Hermetic reciprocating refrigeration compressor for isobutane as refrigerant
8414 30 20		4998803/2020	1359	Hermetic reciprocating compressor, for isobutane as refrigerant: - with the Resistance Start Capacitor Run (RSCR) single phase motor, - with the general coefficient of performance factor not lower than 1,93 at ASHRAE conditions - of the maximum cooling capacity of 150 W or more but not more than 180 W, at ASHRAE conditions	S	New	UNDER EXAMINATION	PL	Applicant	Round 2021-07 For manufacture of household appliances.

8414 30 20	4893260/2020	1120	Hermetic reciprocating refrigeration compressor, for isobutane: - with the brushless permanent magnet 3-phase motor, - having left side suction connection and Power Factor Correction (PFC) inverter, - of the maximum cooling capacity of 150 W or more but not more than 240 W, at ASHRAE conditions	S	New	UNDER EXAMINATION	PL	Applicant	Round 2021-07 For manufacture of household appliances
8414 80 73	5001913/2020	1358	Hermetic heat pump compressor, for R134A or R450A as refrigerant: - with the Single Phase Induction Motor PSC (Permanent Split Capacitor), - having bottom side suction connection and top side discharge connection, - 8,1cm ³ or 8,2cm ³ displacement, - running at 3000 rpm, - of a cooling capacity of 920 W or higher, but not higher than 970 W in ASHRAE conditions	S	New	UNDER EXAMINATION	PL	Applicant	Round 2021-07 For manufacture of household appliances.
8479 90 70	1726342/2020	1901	Rotor part of the mechanical unit ensuring the movement of the camshaft compared to the crankshaft: - with 4 blades that end in grooves, - made of steel alloy with sintering process	S	New	UNDER EXAMINATION	HU	Applicant	Round 2021-07 - roll over request Round 2021-01 - rejected Rotor part of the mechanical unit
8482 40 00	4997507/2020	1107	Axial roller bearing made of steel: - the retainer is made of cold-rolled steel with a carbon content of up to 0,25 percent, complying with standard ASTM A109-98 - the rollers are made of anti-friction steel according to ASTM 295-94, - with an external diameter of 63 mm or more, but not more than 66 mm, - with an internal diameter of 44 mm or more, but not more than 46 mm, - with a weight of 23 g or more, but not more than 27 g, - with 36 or more rollers, but not more than 38 rollers	S	New	UNDER EXAMINATION	HU	Applicant	Round 2021-07 incorporated in an air-conditioning compressor for motor vehicles

8482 99 00		4921841/2020	1303	Steel inner rings with diameters between 14,66 mm and 76,2 mm and outer rings with diameters between 26 mm and 100 mm, with an internal raceway to permit the balls to roll	S		New	UNDER EXAMINATION	PT	Applicant	Round 2021-07 used for the production of one raceway ball bearing
8483 50 80		4997528/2020	1108	Pulley blocks of non-cast steel: - made of structural carbon steel complying with standard JIS G4051, - with an external diameter of 114 mm or more, but not more than 118 mm, - with an internal diameter of 33 mm or more, but not more than 37 mm, - with a width of 29 mm or more, but not more than 33 mm, - with a weight of 0,6 kg or more, but not more than 0,9 kg, - with 6 trapezoidal grooves	S		New	UNDER EXAMINATION	HU	Applicant	Round 2021-07 The imported product is incorporated in an air-conditioning compressor for motor vehicles (classified under the 8414 30 89 20 customs tariff number).
8501 53 50		5002344/2020	1354	Permanent magnet synchronous traction motor, with: - a continuous power of 110 kW or more but not more than 180 kW, - a liquid cooled system, - a total length of 500 mm or more but not more than 650 mm, - a total width of 600 mm or more but not more than 700 mm, - a total height of 550 mm or more but not more than 650 mm, - weighing of not more than 350 kg, - 3 suspension points	S		New	UNDER EXAMINATION	PL	Applicant	Round 2021-07 Synchronous traction motor, generating a moment, which is later transmitted to the wheels of the vehicle.
8501 62 00		5002298/2020	1355	AC, 3-phase generator, with: - a continuous power of 140 kW or more but not more than 210 kW, - a continuous torque of 650 Nm or more but not more than 900 Nm, - a maximum working speed of 2 700 revolutions per minute (rpm), - a liquid cooled system, - a length of 100 mm or more but not more than 200 mm, - a width of 550 mm or more but not more	S		New	UNDER EXAMINATION	PL	Applicant	Round 2021-07 used in the production of buses.

8504 40 88		5002137/2020	1357	than 650 mm, - a height of 550 mm or more but not more than 650 mm, - weighing of not more than 150 kg Main power module of high voltage circuits, with: - DC/AC inverter, - a power greater of 190 kW or more but not more than 220 kW, - a liquid cooled system, - a length of 300 mm or more but not more than 950 mm, - a width of 350 mm or more but not more than 600 mm, - a height of 200 mm or more but not more than 350 mm, - weighing of not more than 90 kg,a possibility of connecting a traction motor, generator and energy storage system	S	New	UNDER EXAMINATION	PL	Applicant	Round 2021-07 Propulsion Control System
8504 40 90		5002230/2020	1356	DC to DC converter, converting energy from a hybrid DC high voltage circuit to DC 28 V, with: - a power of 10 kW or more but not more than 16 kW, - a liquid cooled system,a length of 400 mm or more but not more than 650 mm, - a width of 300 mm or more but not more than 450 mm, - a height of 220 mm or more but not more than 350 mm, - weighing of not more than 50 kg	S	New	UNDER EXAMINATION	PL	Applicant	Round 2021-07 used in a hybrid vehicle instead of alternators, it is used to power 24 V receivers in the vehicle such as pumps, fans, lighting, etc.
8505 90 90		4997492/2020	1106	Electromagnetic clutch coil in a cylindrical metal housing: - the metal housing is made of hot-rolled steel complying with standard JIS G 3131 - SPHE, - the coil is made of copper wire, - with a weight of 0,4 kg or more, but not more than 0,7 kg, - with a width of 22 mm or more, but not	S	New	UNDER EXAMINATION	HU	Applicant	Round 2021-07 Electromagnetic clutch coil in a cylindrical metal housing

8507 60 00			4922932/2020	1124	more than 25 mm, - with an internal diameter of 44 mm or more, but not more than 46 mm, - with an external diameter of 88 mm or more, but not more than 96 mm, - without plunger, - with one connector	S	New		UNDER EXAMINATION	CZ	Applicant	Round 2021-07 Integrated battery system in a metal case with holders
					Integrated battery system in a metal case with holders, consisting of: - a lithium-ion battery with a voltage of 36 V or more but not more than 50,4 V and a nominal energy of 0,6 kWh, - Battery Management System, - a power relay, - a cooling system, - four connectors, for use in the manufacture of Mild-hybrid (mHEV) motor vehicles (1)							
8529 90 92			4952803/2020	1139	CMOS-Image sensor - with a micro lens on every pixel (micro lens coverage at least 99 % of all pixel) - to capture infra-red light reflected from objects in order to capture depth images in a cameras built for distance measurements (Time-of-Flight)	S	New		UNDER EXAMINATION	DE	Applicant	Round 2021-07 CMOS-Image sensor
8537 10 91			5002783/2020	1053	The main hybrid system controller; diagnosing and controlling the elements of the hybrid propulsion system, with: - a programmable memory, - a microprocessor, - at least one composite connector, - a voltage of 24 V, - with a length of 350 mm or more but not more than 400 mm, - with a width of 200 mm or more but not more than 250 mm, - with a height of 80 mm or more but not more than 120 mm,	S	New		UNDER EXAMINATION	PL	Applicant	Round 2021-07 Usage description: The main computer managing the hybrid system is the interface between the hybrid system and the vehicle computer. It provides a diagnosis of the hybrid system of buses

8537 10 98		4944181/2020	1131	- in a metal housing Control panel for car radio and/or navigation control with: - electronic passive components, - at least 2 buttons, - LEDs, - at least 1 connector, - whether or not warning triangle button, for use in the manufacture of goods of Chapter 87 (1)	S		New	UNDER EXAMINATION	SK	Applicant	Round 2021-07 Control panel for car radio and/or navigation control
8544 20 00		4921924/2020	1123	Flexible coaxial cable with - capability of transmitting RF (Radio Frequency) signals in 2G, 3G, 4G, 5G communication systems, - a resistance of 50 Ohm, - an operation frequency between 400 MHz and 18 GHz, - an operation temperature range between - 55 °C and +125 °C, for use in the manufacture of goods under CN code 8517 70 00 (1)	S		New	UNDER EXAMINATION	TR	Applicant	Round 2021-07 Flexible coaxial cable
8708 30 10		4944174/2020	1130	The integrated electric brake unit integrating electronic brake assistants, hydraulic unit driven by brushless electric motor and brake fluid reservoir for immediate generation of the required hydraulic pressure during braking, full electronic brake control and enabling regenerative braking for use in the manufacture of plug-in hybrid passenger cars (1)	S		New	UNDER EXAMINATION	SK	Applicant	Round 2021-07 Integrated electric brake unit
8708 99 97		5003955/2020	1352	A set of Type 4 H2 cylinders, in accordance with the EC 79 standard, consisting of two to eight cylinders on aluminum frames: - cylinders made of high density polyethylene (HDPE) composite reinforced with a braid of glass and carbon fibers in epoxy resin,	S		New	UNDER EXAMINATION	PL	Applicant	Round 2021-07 Hydrogen systems for bus

8708 99 97							- with an operating pressure of not less than 35 MPa, [a maximum filling pressure of not less than 43 MPa and a test pressure of not less than 50 MPa], - with a durability declared by the manufacturer of not less than 20 years, - with a cylinder capacity of 180 liters or more but not more than 375 liters, - equipped with a set of solenoid, manual and safety PRD valves, - with a total width of 1800 mm or more but not more than 2 300 mm, - with a total height of 400 mm or more but not more than 500 mm, - with a total length of 1200 mm or more but not more than 3 600 mm	S	New	UNDER EXAMINATION	PL AT	Applicant Opposed	Round 2021-07 The tank is an integral part of the bus traction engine power supply system
							Stainless steel tank for storage of liquefied methane (LNG) type HLNG-135, in accordance with the R-110 standard: - with an operating pressure of 7 bar or more but not more than 17 bar, - with pressure surges when the power change below 2 bar, - with a minimum methane storage temperature not exceeding -130°C, - with a total capacity of 500 liters or more but not more than 550 liters, - with autonomous pressure regulation in a mechanical way, - equipped with a mechanical shut-off valve, anti-discharge valve, solenoid valve, heat exchanger, operating pressure control valve as well as 16 and 24 bar safety valves, - with the function of combining two tanks into a set, - using vacuum insulation, - with an additional cover to protect against weather, - with a diameter of 550 mm or more but not more than 600 mm, - a length of 3000 mm or more but not more than 3100 mm	1059	5004038/2020				

8708 99 97		5003870/2020	1353	A set of CNG cylinders type CNG-4, in accordance with the ECE R110 standard, consisting of four or five cylinders on aluminum frames: - made of high density polyethylene (HDPE) composite reinforced with a braid of glass and carbon fibers in epoxy resin, - with an operating pressure of not less than 20 MPa, [a maximum filling pressure of not less than 26 MPa and a test pressure of not less than 30 MPa], - with a shelf life declared by the manufacturer of not less than 20 years, - with a cylinder capacity of 315 liters or more but not more than 375 liters, - equipped with a set of solenoid, manual and safety PRD valves, - with a total width of 2200 mm or more but not more than 2 300 mm, - with a total height of 450 mm or more but not more than 460 mm, - with a total length of 3500 mm or more but not more than 3 600 mm	S	New	UNDER EXAMINATION	PL	Applicant	Round 2021-07 CNG systems for bus
9503 00 75		4814991/2020	1112	Printed circuit boards in a square or rectangular shape with: - a body made of plastic, - a potentiometer on the front side which provides voltage control, - coloured cables which are connected to the circuit boards for transmitting commands, for use in the manufacture of toys (cars) (1)	S	New	UNDER EXAMINATION	TR	Applicant	Round 01.07.2020 Printed circuit boards for toy cars and their controllers
9503 00 95		4814935/2020	1111	Sound mechanism with: - a body made of plastic (generally in flesh color), - speaker holes on top of the body, - an insulation tape at the bottom of the	S	New	UNDER EXAMINATION	TR	Applicant	Round 2021-07 Sound mechanisms for use in the manufacture of toys (dolls)

								body, - a mechanism which works with pressing top of the body after the insulation tape is removed, - previously loaded voices to play upon pressing the button, for use in the manufacture of toys (dolls) (1)							
--	--	--	--	--	--	--	--	---	--	--	--	--	--	--	--

ex 1515 90 99	92	1959/1/2002 PROLONG 2019	3110	DE (28.08.2020) new proposal: Vegetable oil, refined or semi-refined, containing by weight 35 % or more but not more than 57 % of arachidonic acid or 35 % or more but not more than 50 % of docosahexaenoic acid ---- Current description: Vegetable oil, refined, containing by weight 35 % or more but not more than 50 % of arachidonic acid or 35 % or more but not more than 50 % of docosahexaenoic acid	S	Amendment	UNDER EXAMINATION	IE ES	Applicant Co-applicant	Round 2021-07 - Request for amendment.
ex 2905 32 00	10	4755930/2018	3604	IE(20.08.2020) new proposal: (2S)-propane-1,2-diol (CAS RN 4254-15-3) with a purity by weight of 98 % or more ---- Current description: (2S)-propane-1,2-diol (CAS RN 4254-15-3)	S	Amendment	UNDER EXAMINATION	IE	Applicant	Round 2021-07- request for amendment. used in the manufacture of bulk Active Pharmaceutical ingredients
ex 2915 90 70	55	450490/2013 PROLONG 2019	3610	IE(15.09.2020) new proposal:Triethyl orthoformate (CAS RN 122-51-0) with a purity by weight of 99 % or more ---- Current description: Triethyl orthoformate (CAS RN 122-51-0)	S	Amendment	UNDER EXAMINATION	FR	Applicant	Round 2021-07 – request for amendment. This raw material is used in the synthesis of the herbicide :>>> Isoxaflutole. This herbicide is mainly used on the corn and on the sugar cane.

ex 2916 13 00	20	3155/3/2000 PROLONG 2019	3602	IE(15.09.2020) new proposal with purity: Zinc Dimethacrylate, in the form of powder (CAS RN 13189-00-9) with a purity by weight of 99 % or more ----- Current description: Zinc dimethacrylate, in the form of powder (CAS RN 13189-00-9)	S	Amendment	UNDER EXAMINATION	FR	Applicant	Round 2021-07 - request for amendment. :
ex 2920 19 00	10	1489/3/1994 PROLONG 2019	3102	Fenitrothion (ISO) (CAS RN 122-14-5)	S	Amendment	UNDER EXAMINATION	NL FR	Applicant Co-applicant	Round 2021-07 - Request for amendment.
ex 2920 19 00	20	1489/2/1994 PROLONG 2019	3103	Tolclofos-methyl (ISO) (CAS RN 57018-04-9)	S	Amendment	UNDER EXAMINATION	FR	Applicant	Round 2021-07 - Request for amendment.
ex 2930 20 00	10	1082/2007	3611	IE(15.09.2020) new proposal: Prosulfocarb (ISO) (CAS RN 52888-80-9) with purity by weight of 97 % or more --- Current description: Prosulfocarb (ISO) (CAS RN 52888-80-9)	S	Amendment	UNDER EXAMINATION	BE	Applicant	Round 2021-07- request for amendment.
ex 2933 29 90	25	311805/2013 PROLONG 2019	3612	IE(15.09.2020) new proposal: Prochloraz (ISO) (CAS RN 67747-09-5) with purity by weight of 97 % or more ----- Current description: Prochloraz (ISO) (CAS RN 67747-09-5)	S	Amendment	UNDER EXAMINATION	DE	Applicant	Round 2021-07 - request for amendment. used primarily for the manufacture of fungicide plant protection products, but also as a disinfectant for cereal seeds.
ex 2933 59 95	89	1242965/2016	3105	BE(15.09.2020)new text proposal: 6-Benzyladenine (CAS RN 1214-39-7) with a purity by weight of 97 % or more ----- Current text: 6-Benzyladenine (CAS RN 1214-39-7)	S	Amendment	UNDER EXAMINATION	BE	Applicant	Round 2021-07 - Request for amendment. used in the manufacture of

ex 3801 10 00	10	1731611/2020	3113	DE(09.09.2020) new proposal: Artificial graphite in powder form, (CAS RN 7782-42-5) with: - or without coating on the surface, - particle size represented by d50 value of 13 µm (± 7), - specific surface area (measured by BET) less than 5,0 m²/g, - tap density: Less than 2g/cm³, - specific Discharge Capacity of 350,0 ± 15 mAh/g, - initial efficiency above 92,0 % ----- Current text: Artificial graphite in powder form, (CAS RN 7782-42-5) with: - a secondary particle structure which is aggregated from smaller primary particles. - without coating on the surface, - particle size represented by d50 value of 13,5 µm (± 0,5), - specific surface area (measured by BET) less than 2,0 m²/g, - tap density: 1,10 ~ 1,70 g/cm³, - specific Discharge Capacity of 351,0 mAh/g (±3,0), - initial efficiency of 94,0 % (± 1,0)	S	Amendment	UNDER EXAMINATION	SE EU	Applicant Opposed	finished plant growth regulator products of tariff heading 3808.
ex 3824 99 93	45	5505061/2016	3001	Sodium hydrogen 3-aminonaphthalene-1,5-disulphonate (CAS RN 4681-22-5) containing by weight: - not more than 20 % of disodium sulphate, and - not more than 10 % of sodium chloride	S	Amendment	UNDER EXAMINATION	CZ	Applicant	Round 2021-07 request for amendment – roll over after CCC decision. About the correct classification.
ex 3920 10 89	30	246973/2011	3107	AT(11.09.2020) new proposal: Ethylene vinyl acetate (EVA) film: - with a raised relief surface with	S	Amendment	UNDER EXAMINATION	DE	Applicant	Round 2021-07- Request for amendment

ex 3920 20 29	94	294101/2011	3601	embossed undulations, - not laminated, - not cross-linked (not cured) and - with a thickness of more than 0,3 mm ----- Current text: Ethylene vinyl acetate (EVA) film with: - a raised relief surface with embossed undulations, and - a thickness of more than 0,125 mm	S	Amendment	UNDER EXAMINATION	IE	Applicant	Round 2021-07 - request for amendment.
ex 6903 90 90	30	3141/3/2000 PROLONG 2019	2801	Current description: Co-extruded trilayer film, - each layer containing a mixture of polypropylene and polyethylene, - containing not more than 3 % by weight of other polymers, - whether or not containing titanium dioxide in the core layer, - of an overall thickness of not more than 70 µm ----- Current description: Co-extruded trilayer film, - each layer containing a mixture of polypropylene and polyethylene, - containing not more than 3 % by weight of other polymers, - whether or not containing titanium dioxide in the core layer, - of an overall thickness of not more than 70 µm	S	Amendment	UNDER EXAMINATION	IT	Applicant	Round 2021-07: Request for amendment related to classification issue.
ex 6909 19 00	40	4699502/2018	3112	PL(11.09.2020) new proposal: Ceramic-carbon absorption or adsorption	S	Amendment	UNDER EXAMINATION	PL	Applicant	Round 2021-07 – Request for

ex 7326 90 98 7907 00 00	40	1143537/2015	3108	cartridges with the following characteristics: - extruded fired ceramic bound multicellular cylindrical structure, - 5 % or more by weight but not more than 70 % by weight of activated carbon, - 30 % or more by weight but no more than 90 % by weight of ceramic binder, - with a diameter of 29 mm or more but no more than 41 mm, - a length of not more than 150 mm, - fired at temperature of 800 °C or more, and - for vapours adsorption, of a kind used for assembly in fuel vapours absorbers or adsorbers in fuel systems of motor vehicles --- Current description: Ceramic-carbon absorption cartridges with the following characteristics: - extruded fired ceramic bound multicellular cylindrical structure, - 10 % or more by weight but not more than 35 % by weight of activated carbon, - 65 % or more by weight but not more than 90 % by weight of ceramic binder, - with a diameter of 29 mm or more but not more than 41 mm, - a length of not more than 150 mm, - fired at temperature of 800 °C or more, and - for vapours adsorption, of a kind used for assembly in fuel vapours absorbers in fuel systems of motor vehicles	S	Amendment	UNDER EXAMINATION	AT	Applicant	amendment. used as hydrocarbons adsorption supports in canisters
										ROUND 2021-07: request for amendment. metal weights with different heaviness, which are built into remote controls to give them better haptic and

ex 7616 99 10 ex 8708 99 10 ex 8708 99 97	30 60 50	3155592/2014 PROLONG 2020	3605	- whether or not with parts of other metals - whether or not surface treated - whether or not printed of a kind used for the production of remote controls ----- Current description: Iron and steel weights - whether or not with parts of other material - whether or not with parts of other metals - whether or not surface treated - whether or not printed of a kind used for the production of remote controls	S	Amendment	UNDER EXAMINATION	PL	Applicant	additional weight Round 2021-07- request for amendment. ROUND 2015-07 Aluminum bracket being the component of the car engine suspension elements
---	----------------	---------------------------------	------	---	---	-----------	-------------------	----	-----------	---

[illegible]

ex 8507 60 00	13	4697852/2018	3607	including electric components and flange with minimum 2 and maximum 11 bore holes) aluminium diecast or sheet steel housing whether or not with a sealing compound (groove with an O-ring and grease), - a stator with single T-tooth design and single coil windings in 9/6 or 12/8 topology, and - surface magnets, - whether or not with electronic power steering controller	S	Amendment	UNDER EXAMINATION	PL EU	Applicant Opposed	Round 2021-07- request for amendment Round 2021-01: review of the measure Mandatory review set to 12.31.2021. Sets cells are used for vehicles with electric motor as motors for propulsion, other than those capable of being charged by plugging to external source of electric power : scooters, cars and buses/coaches
				DE(04.09.2020) new proposal: Prismatic lithium-ion electric accumulator with: - a width of 120,0 mm or more but not more than 305,0 mm - a thickness of 12,0 mm or more but not more than 67,0 mm - a height of 72,0 mm or more but not more than 126,0 mm - a nominal voltage of 3,6 V or more but not more than 3,75 V and - a nominal capacity of 6,9 Ah or more not more than 265 Ah for use in the manufacture of rechargeable electric vehicle (1) ---- Current description: Prismatic lithium-ion electric accumulators with: - a width of 173,0 mm ($\pm 0,3$ mm), - a thickness of 45,0 mm ($\pm 0,3$ mm), - a height 125,0 mm ($\pm 0,3$ mm), - a nominal voltage of 3,67 V ($\pm 0,01$ V), and - a nominal capacity of 94 Ah and/or 120 Ah, for use in the manufacture of rechargeable electric vehicle batteries (1)						

ex 8507 60 00	50	323555/2012	3603	FR(15.09.2020) new text proposal: Modules composed of prismatic type cells (with a parallelepipedal shape and rigid) for the assembly of batteries of ion lithium electric accumulators with: - a length of 450 mm or more, but not more than 500 mm, - a width of 100 mm or more, but not more than 130 mm, - a height of 50 mm or more, but not more than 120 mm, - a weight of 3,6 kg or more, but not more than 9,5 kg, and - an energy of 620 Wh or more, but not more than 2 158 Wh --- Current description: Modules for the assembly of batteries of ion lithium electric accumulators with: - a length of 298 mm or more, but not more than 500 mm, - a width of 33,5 mm or more, but not more than 209 mm, - a height of 75 mm or more, but not more than 228 mm, - a weight of 3,6 kg or more, but not more than 17 kg, and - a nominal energy of 458 Wh or more, but not more than 2 158 Wh	S	Amendment	UNDER EXAMINATION	FR EU	Applicant Opposed	Round 2021-07: request for amendment. Round 2021-01: review of the measure (new date for mandatory review 12.31.2021) Modules intended for the assembly of a rechargeable battery for the supply of power to electric motor vehicles
ex 8507 60 00	75	984116/2011	3608	DE(04.09.2020): Rectangular lithium-ion-accumulator with: - a metal casing, - a length between 148mm and 173 mm (±0,15 mm), - a width between 17,5 mm and 21 mm (±0,1 mm), - a height between 91 mm and 95mm (±0,15 mm), - a nominal voltage between 3,3 V and 3,65 V and - a nominal capacity of 17,5 Ah or more ----	S	Amendment	UNDER EXAMINATION	AT EU	Applicant Opposed	Round 2021-07: Amendment. The accumulators are used for the production of rechargeable batteries